

# Kubernetes

- [Plex Media Server - Volume Mounting](#)
- [k3s - Multiple network interfaces](#)
- [Plex Media Server - iGPU Mounting](#)

# Plex Media Server - Volume Mounting

Reference: <https://www.plex.tv/blog/plex-pro-week-23-a-z-on-k8s-for-plex-media-server/>

Reference: <https://github.com/plexinc/pms-docker/tree/master/charts/plex-media-server>

Mounting CIFS Volume to PMS on Kubernetes (values).

```
rclone:
  # if the rclone sidecar should be created
  enabled: true

  # The name of the secret that contains the rclone configuration file.
  # The key must be called `rclone.conf` in the secret
  configSecret: "plex-rconf"

  # the remote drive that should be mounted using rclone
  # this must be in the form of `name:[/optional/path]`
  # this remote will be mounted at `/data/name` in the PMS container
  remotes:
    - video:/video

  # if the remote volumes should be mounted as read only
  readOnly: true
```

rclone.conf must be a secret in the following format (anonymous access):

```
apiVersion: v1
kind: Secret
metadata:
  name: plex-rconf
type: Opaque
stringData:
  rclone.conf: |
    [video]
```

```
type = smb  
host = 10.10.10.10  
user = guest
```

Effectivly mounting \\10.10.10.10\video

# k3s - Multiple network interfaces

k3s will pick the first address it finds as node ip.

Adding `--flannel-iface` and/or `--node-ip` will allow to configure the addresses.

Reference: <https://docs.k3s.io/cli/server>

Removing gateway from all interfaces except one will be chosen as default route.

# Plex Media Server - iGPU Mounting

/dev/dri mounted through container for iGPU usage

```
# Optionally specify additional volume mounts for the PMS and init containers.
```

```
extraVolumeMounts:
```

```
- name: dev-dri
```

```
  mountPath: /dev/dri
```

```
# extraVolumeMounts:
```

```
# - name: some-volume-name
```

```
#   mountPath: /path/in/container
```

```
# Optionally specify additional volumes for the pod.
```

```
extraVolumes:
```

```
- name: dev-dri
```

```
  hostPath:
```

```
    path: /dev/dri
```

```
# extraVolumes:
```

```
# - name: some-volume-name
```

```
#   emptyDir: {}
```

Reference: <https://github.com/plexinc/pms-docker/tree/master/charts/plex-media-server>