

# Plex Media Server - Volume Mounting

Reference: <https://www.plex.tv/blog/plex-pro-week-23-a-z-on-k8s-for-plex-media-server/>

Reference: <https://github.com/plexinc/pms-docker/tree/master/charts/plex-media-server>

Mounting CIFS Volume to PMS on Kubernetes (values).

```
rclone:
  # if the rclone sidecar should be created
  enabled: true

  # The name of the secret that contains the rclone configuration file.
  # The key must be called `rclone.conf` in the secret
  configSecret: "plex-rconf"

  # the remote drive that should be mounted using rclone
  # this must be in the form of `name:[/optional/path]`
  # this remote will be mounted at `/data/name` in the PMS container
  remotes:
    - video:/video

  # if the remote volumes should be mounted as read only
  readOnly: true
```

rclone.conf must be a secret in the following format (anonymous access):

```
apiVersion: v1
kind: Secret
metadata:
  name: plex-rconf
type: Opaque
stringData:
  rclone.conf: |
    [video]
    type = smb
```

```
host = 10.10.10.10
```

```
user = guest
```

Effectively mounting \\10.10.10.10\video

---

Revision #2

Created 7 September 2024 14:02:57 by XeroX

Updated 7 September 2024 14:07:27 by XeroX